

## Universal Supply Air Damper 3-Wire Power Open/Close

- DEPENDABLE POWER OPEN/POWER CLOSE/MODULATING
- LED INDICATORS FOR FULL OPEN AND CLOSED POSITIONS
- LED INDICATORS FLASH WHEN BLADE IS MOVING
- INSULATION PAD UNDER MOTOR REDUCES CONDENSATION
- AVAILABLE SIZES: 8 x 8 up to 30 x 30 & CUSTOM SIZES
- LONG-LIFE ACTUATOR
- 5 YEAR FACTORY WARRANTY
- WORKS WITH MOST AFTERMARKET ZONING SYSTEMS
- WORKS WITH CARRIER/BRYANT/ION ZONING SYSTEMS



The XCI RPUCA-series low pressure two-position & modulating damper was developed for precise control of supply air in the HVAC duct system. Rigid aluminum components provide a strong, yet lightweight construction. The damper actuator with built-in LED lights is designed for years of care-free operation. The power open/power close design guarantees precise control of supply air into each zone. Long-life nylon gears drive the opposed blades open and closed. Opposed blade design reduces turbulence in the air stream. 15 Second operation to full open or closed position. A minimum open position can be set to bleed air for ventilation or duct balancing. End of shaft marked with high-visibility blade position indicator. Custom sizes are available. Quick turnaround on orders. Most orders ship the same day.

- **QUALITY DESIGN**
- **SUPERIOR FEATURES**
- **SLIP-IN INSTALLATION**
- **SIDE MOUNT OR TOP/BOTTOM MOUNT**

### SPECIFICATIONS

<b>Power</b>	24VAC, 2 VA typical (3 VA Max)
<b>Actuator</b>	XCI POCM Brushless Motor Design 10 in-lb Torque Power-Open/Power-Close 15 Second Operation Cycle Max 90 Degree Travel
<b>Indicator</b>	LED Indicates Full Open or Close Blink When Opening & Closing
<b>Wiring</b>	3 Screw Terminals PO, PC, Common Use 18/3 Solid Core Wire



