

## SPECIFICATION SHEET

## **RSRDA**

An ISO 9001:2015 Company

- **DEPENDABLE POWER CLOSE/SPRING OPEN**
- LED INDICATOR SHOWS WHEN DAMPER IS POWERED
- OPPOSED BLADE DESIGN FOR BETTER AIRFLOW CONTROL
- AVAILABLE SIZES: 8 x 8 up to 30 x 30
- **LONG-LIFE ACTUATOR**
- **5 YEAR FACTORY WARRANTY**

- **QUALITY DESIGN**
- **SUPERIOR FEATURES**
- **FLEXIBLE INSTALLATION**

## **GENERAL DESCRIPTION**

The XCI RSRDA-series low pressure two-position damper was developed for precise control of supply air in the HVAC duct system. Rigid aluminum components provide a strong, yet lightweight construction. The damper actuator is designed for years of care-free operation. Bright red LED indicates when damper is powered. The power close/spring open design guarantees precise control of supply air into each zone. Long-life nylon gears drive the opposed blades open and closed. Opposed blade design reduces turbulence in the air stream. 30 Second operation to full closed position. Custom sizes are available.



## **SPECIFICATIONS**

24VAC, 8 VA typical (10 VA Max) **Power** 

Actuator XCI POCA

Indicator

**Brushless Motor Design** 

10 in-lb Torque

Power-Close/Spring-Open 30 Second Open Cycle

Max 90 Degree Travel

**LED Indicates Power** 2 Screwless Terminals Wiring

Use 18/2 Solid Core Wire